

## SELECT RANGE CAMERA MONITOR SYSTEM

Single camera system for rigid vehicles  
(Includes 20m camera extension cable)  
Single camera system for smaller buses and mini-buses  
(Includes 10m camera extension cable)



- VBV-750DM - monitor
- VBV-700C - camera
- 2 year warranty



- Monitor**
- 12-24Vdc
  - 3 camera inputs
  - Size (WxHxD)  
148 x 110 x 32mm

- Camera**
- Viewing angle (HxVxD)  
98 x 75 x 120°
  - IP67
  - Size (WxHxD)  
88 x 85 x 66mm

See individual products for detailed specifications

## NEW DIGITAL

## SELECT RANGE MONITOR



5" Digital LCD monitor

- 12-24Vdc
- 3 camera inputs
- Size (WxHxD)  
148 x 110 x 31.5mm
- 2 year warranty



- Features**
- 3 Auto-triggers
  - Mirror / Normal switching from menu
  - On-screen distance markers
  - Audio
  - Sun shield
  - Auto-dimmer
  - Multi-lingual menus
  - Auto-switching PAL / NTSC

- Picture Quality**
- Anti-glare screen
  - Resolution: 640 x 3 x 480
  - Contrast ratio: 500:1
  - Brightness: 200cd/m<sup>2</sup>

- Viewing angles:  
Side 70° x Top 50° x Bottom 70°
- Power**
- Power consumption: 5 Watts
  - Current: 0.18 Amps

- Durability & Standards**
- Mechanical vibration: 10G
  - Mechanical shock: 100G
  - Operating temperature: -20 to +70°C
  - CE marked
  - EMC approved: e
  - Approved for indirect vision
  - HALT tested

## ELITE RANGE CAMERA



Compact flush mount camera  
Rear view (high mount - mirror view)

- Viewing angle (HxVxD)  
95 x 72 x 125°
- IP68
- Size (WxHxD)  
50 x 45 x 65mm
- 3 year warranty



- Features**
- 1/3" Sony CCD
  - TV System: PAL
  - TV Lines: 420

- Power**
- Power consumption: 1.2 Watts
  - Current: 0.1 Amps

- Durability & Standards**
- Mechanical vibration: 20G
  - Mechanical shock: 100G
  - Operating temperature: -30 to +80°C
  - CE marked
  - EMC approved: e
  - Approved for indirect vision
  - HALT tested



## ELITE RANGE CAMERA CABLE

20 metre cable  
10 metre cable